## Data Sheet for LCT01-150A

1. Description: This small size current transformer is excellent in measurement accuracy and the electrical properties should meet following requirements. 2. Working Condition: Environmental Temperature: -10~50°C Atmospheric Pressure: 86~106Kpa Relative Humidity: ≤95% 3. Electric Index: 3.1 Applicable Frequency 50~100Hz 3.2 Rated Primary Current AC: 150A 3.3 Rated Secondary Current AC: 0.15A 3.4 Power 0.4 VA 3.5 Precision Class 3 3.6 Direct Resistance  $\leq$ 28 ohms (Test Temperature: 10~40°C) 3.7 Inductance ≥3.6H (Test Conditions: SER 100Hz) 3.8 Circuit test  $RL=43.3\Omega$ 1000Ts 3.9 Temperature ≤75°C (Under Rated Current) 3.10 Insulation Resistance  $\geq 100 \text{M}\Omega$ (a) 500VDC 3.11 Dielectric Strength AC 4000V 5mA 60S 4. Appearance and Structure: Weight: 31g±5% Appearance and Structure Encapsulating 30 14, 5 Materials ф 10.80 **GLORIA** 0 ф 0.80

## **American Toppower**

Add: 2033 Route 130, Unit N, Monmouth Junction, NJ 08852

Phone: 732-821-1000 Fax: 732-821-2000 E-mail: Sales@americantoppower.com

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.