


Data Sheet for T-2/3A600

Specifications


Type :	Rechargeable Nickel Cadmium Standard Cell
Model (P/N) :	T-2/3A600
Nominal Dimension : (with sleeve)	$\phi = 17.0^{0}_{-0.5}$ mm H = 29.0 ± 0.5 mm
Applications :	Recommended discharge current 60 to 600 mA
Nominal Voltage :	1.2V
Nominal Capacity :	600 mAh when discharge at 120 mA to 1.0 V at 20°C
Standard Charge :	60 mA for 15 hrs at 20°C
Fast Charge :	240 mA (0.4C) with charge termination control Recommended control parameters Timer: 140 % nominal input
Service Life :	> 500 cycles
Continuous Overcharge :	60 mA maximum permissible current No conspicuous deformation and / or leakage
Weight :	18 g
Internal Resistance :	Max 35 m Ω at 1000 Hz measured within 1 hour after standard charge
Max. Charging Voltage :	1.5 V at 60 mA charging
Ambient Temperature Range	Standard Charge : 0°C to 45°C Fast Charge : 10°C to 45°C Discharge : -20°C to 45°C Storage : -20°C to 45°C

Characteristics

Charge Curves (20 °C)



Discharge Curves (20 °C)



Charge/Discharge Efficiency vs. Temperature

